

EFB Elektronik EFB-Elektronik - SFP (Mini-GBIC)-Transceiver-Modul (gleichwertig mit: Cisco GLC-SX-MMD)

1GbE - Fibre Channel - 1000Base-SX - LC Multi-Mode - bis zu 550 m - 850 nm - für Cisco 38XX; Catalyst 3560 - ESS9300; Integrated Services Router 11XX; Nexus 93XX - 93XXX

Gruppe	Zubehör Netzwerk
Hersteller	EFB Elektronik
Hersteller Art. Nr.	SFP1000SX
EAN/UPC	4049759255466



Beschreibung

EFB-Elektronik - SFP (Mini-GBIC)-Transceiver-Modul (gleichwertig mit: Cisco GLC-SX-MMD) - 1GbE, Fibre Channel - 1000Base-SX - LC Multi-Mode - bis zu 550 m - 850 nm - für Cisco 38XX; Catalyst 3560, ESS9300; Integrated Services Router 11XX; Nexus 93XX, 93XXX

Hauptmerkmale

Produktbeschreibung	EFB-Elektronik - SFP (Mini-GBIC)-Transceiver-Modul - 1GbE, Fibre Channel
Gerätetyp	SFP (Mini-GBIC)-Transceiver-Modul - LC Multi-Mode
Formfaktor	Plug-in-Modul
Verdrahtungstyp	1000Base-SX
Datenübertragungsrate	1.25 Gbps
Optische Wellenlänge	850 nm
Data Link Protocol	1GbE, Fibre Channel
Maximaler Übertragungsbereich	550 m
Gleichwertige OEM-Herstellerteilenummer	Cisco GLC-SX-MMD
Entwickelt für	Cisco 38XX, 38XX V3PN, 7301, 7301 VAM2+; Catalyst 29XX, 3560, 3750, 4500, 4948, ESS9300; Catalyst Compact 2960; Catalyst Express 500; CSS 11XXX; Integrated Services Router 11XX; ME 3400, 4924, 6524; Nexus 93XX, 93XXX; Supervisor Engine 720, II-Plus-TS

Ausführliche Details

Allgemein	
Gerätetyp	SFP (Mini-GBIC)-Transceiver-Modul
Formfaktor	Plug-in-Modul
Netzwerk	
Anschlussstechnik	Kabelgebunden

Verdrahtungstyp	1000Base-SX
Data Link Protocol	1GbE, Fibre Channel
Datenübertragungsrate	1.25 Gbps
Optische Wellenlänge	850 nm
Maximaler Übertragungsbereich	550 m
Leistungsmerkmale	Digital Diagnostics Monitoring (DDM), Vertical Cavity Surface Emitting Laser (VCSEL)
	Erweiterung/Konnektivität
Schnittstellen	1 x Fibre Channel / Ethernet 1000Base-SX - LC multi-mode weiblich x 2
	Verschiedenes
Kennzeichnung	RoHS
Gleichwertige OEM-Herstellerteilennummer	Cisco GLC-SX-MMD
	Herstellergarantie
Service und Support	Begrenzte Garantie - 1 Jahr
	Umgebungsbedingungen
Min Betriebstemperatur	0 °C
Max. Betriebstemperatur	70 °C
	Informationen zur Kompatibilität
Entwickelt für	Cisco 3825, 3825 Branch Office in a Box Bundle, 3825 HVSEC Bundle, 3825 ISR IP Video Surveillance Bundle, 3825 Retail Bundle, 3825 Secure WAN Optimization Bundle, 3825 SRST Voice Upgrades for HSEC Bundle, 3825 Unified Communications Bundle, 3825 Unified Communications Bundle with Advanced Security, 3825 Video Encoding Bundle, 3825 VSEC Bundle, 3825 WAN Application Acceleration Bundle, 3825 WAN Optimization Bundle, 3825C, 3845, 3845 Branch Office in a Box Bundle, 3845 HVSEC Bundle, 3845 ISR IP Video Surveillance Bundle, 3845 Unified Communications Bundle, 3845 Unified Communications Bundle with Advanced Security, 3845 Video Encoding Bundle, 3845 VSEC Bundle, 3845 WAN Application Acceleration Bundle, 3845 WAN Optimization Bundle, 3845C, 7301 VAM2+ Router Security Bundle Cisco Catalyst 2960-24LC-S, 2960-24PC-L, 2960-24PC-S, 2960-24TC-L, 2960-24TC-S, 2960-48PST-L, 2960-48PST-S, 2960-48T, 2960-48TC-L, 2960-48TC-S, 2960-8TC-S, 2960S-24PD-L, 2960S-24PS-L, 2960S-24TD-L, 2960S-24TS-L, 2960S-24TS-S, 2960S-48FPD-L, 2960S-48FPS-L, 2960S-48LPD-L, 2960S-48LPS-L, 2960S-48TD-L, 2960S-48TS-L, 2960S-48TS-S, 3560-12PC, 3560-12PC-S, 3560-24TS, 3560-48TS, 3560E-12D, 3560E-12SD-E, 3560E-12SD-S, 3560E-24TD, 3560E-48PD, 3560E-48PD-F, 3560E-48TD, 3560E-48TD-SD, 3560G-48, 3560V2-24PS, 3560V2-24TS, 3560V2-24TS-SD, 3560V2-48PS, 3560V2-48TS, 3560X-24P-E, 3560X-24P-L, 3560X-24P-S, 3560X-24T-10G, 3560X-24T-E, 3560X-24T-L, 3560X-24T-S, 3560X-24U-E, 3560X-48P-E, 3560X-48PF-10G, 3560X-48PF-E, 3560X-48PF-L, 3560X-48PF-S, 3560X-48P-L, 3560X-48P-S, 3560X-48T-E, 3560X-48T-L, 3560X-48T-S, 3560X-48U-E, 3560X-48U-L, 3560X-48U-S, 3750G-12S-S, 3750G-24PS-E, 3750G-24PS-S, 3750G-48PS-E, 3750G-48PS-S, 3750G-48TS-E, 3750G-48TS-S, ESS9300 Embedded Series Cisco Catalyst Compact 2960C-8TC-L Cisco Integrated Services Router 1111, 1112, 1113, 1116, 1117, 1118 Cisco ME 4924-10GE, 6524 Ethernet Switch Cisco Nexus 93108TC-EX, 93180YC-FX, 9336C-FX2, 9372PX-E

Technische Daten © 1WorldSync. Technische Änderungen und Irrtümer vorbehalten.